SOLID STATE OPTRONICS



AD4C113

1 Form A / 1 Form B
400V / 35 Ω
MOSFET Output Solid State Relay

Description


The AD4C113 is composed of two isolated relays; one normally open and one normally closed. Each relay has a bi-directional, single-pole, single-throw contact. Completely independent of its counterpart, each consists of an LED driver that activates an integrated circuit, which in turn drives a pair of DMOS transistors. These transistors are protected with free-wheeling diodes that can handle up to 1.5A of inrush current, making the relay ideal for switching lamps and highly inductive loads.

The AD4C113 comes standard in a miniature 8 pin DIP package making it ideal for high-density board applications.

Applications

- Meter Reading Systems
- Multiplexers
- Data Acquisition
- Medical Equipment
- Battery Monitoring
- Home / Safety Security Systems

Schematic Diagram



AD4C113

NC: Normally Closed (Form B)

NO: Normally Open (Form A)

Features

- 1 Form A / 1 Form B Integrated in 1 Package
- Low Input Control Current (1.5mA TYP)
- 120mA Maximum Continuous Load Current
- Low On Resistance (35Ω MAX – Both Poles)
- High Isolation Voltage (2.5kV$_{RMS}$, 3.75kV$_{RMS}$ -H Option)
- Long Life / High Reliability
- RoHS / Pb-Free / REACH Compliant

Agency Approvals

UL/C-UL:	File # E201932
VDE:	File # 40035191 (EN 60747-5-2)

Absolute Maximum Ratings

The values indicated are absolute stress ratings. Functional operation of the device is not implied at these or any conditions in excess of those defined in electrical characteristics section of this document. Exposure to absolute Maximum Ratings may cause permanent damage to the device and may adversely affect reliability.

Storage Temperature	-55 to +125°C
Operating Temperature	-40 to +85°C
Continuous Input Current	50mA
Transient Input Current	500mA
Reverse Input Control Voltage	6V
Input Power Dissipation	40mW
Output Power Dissipation	800mW
Solder Temperature – Wave (10sec)	260°C
Solder Temperature – IR Reflow (10sec)	260°C

Ordering Information

Part Number	Description
AD4C113	8 pin DIP, (50/Tube)
AD4C113-H	3.75kV$_{RMS}$ Viso, 8 pin DIP, (50/Tube)
AD4C113-S	8 pin SMD, (50/Tube)
AD4C113-HS	3.75kV$_{RMS}$, 8 pin SMD, (50/Tube)
AD4C113-STR	8 pin SMD, Tape and Reel (1000/Reel)
AD4C113-HSTR	3.75kV$_{RMS}$, 8 pin SMD, Tape and Reel (1000/Reel)

NOTE: Suffixes listed above are not included in marking on device for part number identification

© 2012 Solid State Optronics • San José, CA

Electrical Characteristics, T_A = 25°C (unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Input Specifications						
LED Forward Voltage	V_F	-	1.2	1.5	V	I_F = 10mA
LED Reverse Voltage	BV_R	6	-	-	V	I_R = 10µA
Turn-On Current (Form A – Normally Open)	$I_{F(NO)}$	-	1.5	5	mA	I_O = 120mA
Turn-On Current (Form B – Normally Closed)	$I_{F(NC)}$	-	0.5	-	mA	I_O = 120mA
Turn-Off Current (Form A – Normally Open)	$I_{FOFF(NO)}$	-	0.5	-	mA	I_O = 120mA
Turn-Off Current (Form B – Normally Open)	$I_{FOFF(NC)}$	-	1.5	5	mA	I_O = 120mA
Output Specifications – Form A (Normally Open)						
Blocking Voltage	V_B	400	-	-	V	I_O=1µA
Continuous Load Current	I_O	-	-	120	mA	I_F=5mA
On Resistance	R_{ON}	-	19.5	35	Ω	I_F=5mA, I_O=120mA
Leakage Current	I_{Oleak}	-	0.2	1	µA	I_F=0mA, V_O=400V
Output Capacitance	C_{OUT}	-	10	-	pF	V_O=25V, f=1.0MHz
Offset Voltage	V_{OFFSET}	-	-	0.2	mV	I_F=5mA
Turn-On Time	T_{ON}	-	1	5	mS	I_F=5mA, I_O=120mA
Turn-Off Time	T_{OFF}	-	0.05	5	mS	I_F=0mA, I_O=120mA
Output Specifications – Form B (Normally Closed)						
Blocking Voltage	V_B	400	-	-	V	I_F=5mA, I_O=1µA
Continuous Load Current	I_O	-	-	120	mA	I_F=0mA
On Resistance	R_{ON}	-	19.5	35	Ω	I_F=0mA, I_O=120mA
Leakage Current	I_{Oleak}	-	0.2	1	µA	I_F=5mA, V_O=400V
Output Capacitance	C_{OUT}	-	10	-	pF	V_O=25V, f=1.0MHz, I_F=5mA
Offset Voltage	V_{OFFSET}	-	-	0.2	mV	I_F=0mA
Turn-On Time	T_{ON}	-	0.1	5	mS	I_F=0mA, I_O=120mA
Turn-Off Time	T_{OFF}	-	1	5	mS	I_F=5mA, I_O=120mA
Coupled Specifications						
Coupled Capacitance	$C_{COUPLED}$	-	3	-	pF	
Contact Transient Ratio	-	2,000	7,000	0	V/µS	dV = 50V
Isolation Specifications						
Isolation Voltage	V_{ISO}	2,500	-	-	V_{RMS}	RH ≤ 50%, t=1min
-H Option	V_{ISO}	3,750	-	-	V_{RMS}	RH ≤ 50%, t=1min
Input-Output Resistance	R_{I-O}	-	10^{12}	-	Ω	V_{I-O} = 500V_{DC}

© 2012 Solid State Optronics • San José, CA

AD4C113 Performance & Characteristics Plots, T_A = 25°C (unless otherwise specified)

Figure 1: *Normally Open*
Typical Turn-On Time Distribution
(N = 100, T_a = 25ºC)




Figure 2: *Normally Open*
Typical Turn-Off Time Distribution
(N = 100, T_a = 25ºC)




Figure 3: *Normally Open*
Typical On-Resistance Distribution
(N = 100, T_a = 25ºC)




Figure 4: *Normally Open*
Typical Output Leakage Current Distribution
(N = 100, T_a = 25ºC)




Figure 5: *Normally Open*
Typical Blocking Voltage Distribution
(N = 100, Ta = 25ºC)





Figure 6: *Normally Open*
Maximum Load Current vs. Temperature



© 2012 Solid State Optronics • San José, CA

AD4C113 Performance & Characteristics Plots, Cont… T_A = 25°C (unless otherwise specified)

Figure 7: *Normally Closed*
Typical Turn-On Time Distribution
(N = 100, T_a = 25ºC)




Figure 8: *Normally Closed*
Typical Turn-Off Time Distribution
(N = 100, T_a = 25ºC)




Figure 9: *Normally Closed*
Typical On-Resistance Distribution
(N = 100, T_a = 25ºC)




Figure 10: *Normally Closed*
Typical Output Leakage Current Distribution
(N = 100, T_a = 25ºC)




Figure 11: *Normally Closed*
Typical Blocking Voltage Distribution
(N = 100, Ta = 25ºC)





Figure 12: *Normally Closed*
Maximum Load Current vs. Temperature



AD4C113 Solder Temperature Profile Recommendations

(1) *Infrared Reflow:*

Refer to the following figure as an example of an optimal temperature profile for single occurrence infrared reflow. Soldering process should not exceed temperature or time limits expressed herein. Surface temperature of device package should not exceed 250ºC:




Figure 1

Process Step	Description	Parameter
A	Preheat Start Temperature (ºC)	150ºC
B	Preheat Finish Temperature (ºC)	180ºC
C	Preheat Time (s)	90 - 120s
D	Melting Temperature (ºC)	230ºC
E	Time above Melting Temperature (s)	30s
F	Peak Temperature, at Terminal (ºC)	260ºC
G	Dwell Time at Peak Temperature (s)	10s
H	Cool-down (ºC/s)	<6ºC/s

(2) *Wave Solder:*

Maximum Temperature:	260ºC (at terminal)
Maximum Time:	10s
Pre-heating:	100 - 150ºC (30 - 90s)
Single Occurrence	

(3) *Hand Solder:*


Maximum Temperature:	350ºC (at tip of soldering iron)
Maximum Time:	3s
Single Occurrence	

© 2012 Solid State Optronics • San José, CA

AD4C113 Package Dimensions

8 PIN DIP Package

Note: *All dimensions in inches ["] with millimeters in parenthesis ()*
Device Weight: 0.45g




© 2012 Solid State Optronics • San José, CA

AD4C113 Package Dimensions

8 PIN SMD Surface Mount Package (-S)

Note: *All dimensions in inches ["] with millimeters in parenthesis ()*

Device Weight: 0.45g




AD4C113 Package Dimensions

8 PIN SMD Tape & Reel (-STR)


Note: *All dimensions in millimeters*

Outline and Dimension (Tape)



W	B	B1	P	P1	K	E	T	D	D1
16.00 ±0.1	10.50 ±0.1	10.30 ±0.1	12.00 ±0.1	4.00 ±0.1	5.00 ±0.1	1.75 ±0.1	0.40 ±0.1	1.50 ±0.1	1.50 ±0.1


Outline and Dimensions (Reel)



Packaging: 1,000 pcs / reel

L	M	N	O	Q	R	S
330.00	100.00	16.40 +0.2	2.00 ±0.1	13.00 ±0.2	2.00	10.00

AD4C113 Package Marking



DISCLAIMER

Solid State Optronics (SSO) makes no warranties or representations with regards to the completeness and accuracy of this document. SSO reserves the right to make changes to product description, specifications at any time without further notices.
SSO shall not assume any liability arising out of the application or use of any product or circuit described herein. Neither circuit patent licenses nor indemnity are expressed or implied.
Except as specified in SSO's Standard Terms & Conditions, SSO disclaims liability for consequential or other damage, and we make no other warranty, expressed or implied, including merchantability and fitness for particular use.

LIFE SUPPORT POLICY

SSO does not authorize use of its devices in life support applications wherein failure or malfunction of a device may lead to personal injury or death. Users of SSO devices in life support applications assume all risks of such use and agree to indemnify SSO against any and all damages resulting from such use. Life support devices are defined as devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when used properly in accordance with instructions for use can be reasonably expected to result in significant injury to the user, or (d) a critical component of a life support device or system whose failure can be reasonably expected to cause failure of the life support device or system, or to affect its safety or effectiveness.

© 2012 Solid State Optronics • San José, CA