SOLID STATE OPTRONICS



SMQ4101

Quad 1 Form A
400V / 35Ω
MOSFET Output Solid State Relay

Description


The SMQ4101 is a bi-directional, quad-pole, single-throw, normally open MOSFET output solid-state relay. This device offers four discrete and independently controlled optically isolated SSRs in one miniature 16 pin SOIC package. Each discrete relay consists of an infrared LED, optically coupled to a Photo Diode Array, which in turn drives a pair of back-to-back enhancement MOSFETs.

The SMQ4101 comes standard in a 16 SOIC package.

Applications

- Data Acquisition
- Meter Reading Systems
- Medical Equipment
- Battery Monitoring
- Multiplexers

Schematic Diagram



SMQ4101

Features

- Quad Pole Switching / Small 16 SOIC Package
- Low On Resistance (35Ω MAX – All Poles)
- 120mA Maximum Continuous Load Current
- High Isolation Voltage (2.5kV$_{RMS}$)
- Long Life / High Reliability
- RoHS / Pb-Free / REACH Compliant

Agency Approvals

UL / C-UL:	File # E201932
VDE:	File # 40035191 (EN 60747-5-2)

Absolute Maximum Ratings

The values indicated are absolute stress ratings. Functional operation of the device is not implied at these or any conditions in excess of those defined in electrical characteristics section of this document. Exposure to absolute Maximum Ratings may cause permanent damage to the device and may adversely affect reliability.

Storage Temperature .....-55 to +125°C
Operating Temperature .....-40 to +85°C
Continuous Input Current.....40mA
Transient Input Current.....400mA
Reverse Input Control Voltage 5V
Input Power Dissipation.....70mW
Total Power Dissipation 500mW
Solder Temperature – Wave (10sec).....260°C
Solder Temperature – IR Reflow (10sec).....260°C

Ordering Information

Part Number	Description
SMQ4101	16 pin SOIC, (46/Tube)
SMQ4101-TR	16 pin SOIC, Tape and Reel (1000/Reel)

NOTE: Suffixes listed above are not included in marking on device for part number identification

© 2014 Solid State Optronics • San José, CA

Electrical Characteristics, T_A = 25°C (unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Input Specifications						
LED Forward Voltage	V_F	-	1.2	1.5	V	I_F = 10mA
LED Reverse Voltage	BV_R	5	-	-	V	I_R = 10µA
Turn-On Current (LED Trigger)	I_F	-	2.5	5	mA	I_O = 120mA
Turn-Off Current	I_{FOFF}	-	0.5	-	mA	I_O = 120mA
Terminal Capacitance	C_t	-	30	-	pF	V=0, f=1MHz
Output Specifications						
Blocking Voltage	V_B	400	-	-	V	I_F=0mA, I_O=1µA
Continuous Load Current	I_O	-	-	120	mA	I_F=5mA
On Resistance	R_{ON}	-	20	35	Ω	I_F=5mA, I_O=120mA
Leakage Current	I_{Oleak}	-	0.2	1	µA	V_O=400V
Output Capacitance	C_{OUT}	-	20	-	pF	I_F=0mA, f=1.0MHz
Offset Voltage	V_{OFFSET}	-	-	0.2	mV	I_F=5mA
Coupled Specifications						
Turn-On Time	T_{ON}	-	1.5	5	mS	I_F=5mA, I_O=120mA
Turn-Off Time	T_{OFF}	-	0.05	0.5	mS	I_F=0mA, I_O=120mA
Input to Output Capacitance	C_S	-	3	-	pF	V=0, f=1MHz
Contact Transient Ratio	-	2,000	7,000	0	V/µS	dV = 50V
Isolation Specifications						
Isolation Voltage	V_{ISO}	2500	-	-	V_{RMS}	RH ≤ 50%, t=1min
Input-Output Resistance	R_{I-O}	-	10^{12}	-	Ω	RH ≤ 50%, V_{I-O} = 500V_{DC}

© 2014 Solid State Optronics • San José, CA

SMQ4101 Performance & Characteristics Plots, T_A = 25°C (unless otherwise specified)

Figure 1: *Typical Turn-On Time Distribution*
(N = 100, T_a = 25ºC)




Figure 2: *Typical Turn-Off Time Distribution*
(N = 100, T_a = 25ºC)




Figure 3: *Typical On-Resistance Distribution*
(N = 100, T_a = 25ºC)




Figure 4: *Typical Output Leakage Current Distribution* (N = 100, T_a = 25ºC)




Figure 5: *Typical Blocking Voltage Distribution*
(N = 100, Ta = 25ºC)





Figure 6: *Maximum Load Current vs. Temperature*




© 2014 Solid State Optronics • San José, CA

SMQ4101 Solder Reflow Temperature Profile Recommendations

(1) *Infrared Reflow:*

Refer to the following figure as an example of an optimal temperature profile for single occurrence infrared reflow. Soldering process should not exceed temperature or time limits expressed herein. Surface temperature of device package should not exceed 250ºC:



Process Step	Description	Parameter
A	Preheat Start Temperature (ºC)	150ºC
B	Preheat Finish Temperature (ºC)	180ºC
C	Preheat Time (s)	90 - 120s
D	Melting Temperature (ºC)	230ºC
E	Time above Melting Temperature (s)	30s
F	Peak Temperature, at Terminal (ºC)	260ºC
G	Dwell Time at Peak Temperature (s)	10s
H	Cool-down (ºC/s)	<6ºC/s

(2) *Wave Solder:*

Maximum Temperature:	260ºC (at terminal)
Maximum Time:	10s
Pre-heating:	100 - 150ºC (30 - 90s)
Single Occurrence	

(3) *Hand Solder:*


Maximum Temperature:	350ºC (at tip of soldering iron)
Maximum Time:	3s
Single Occurrence	

© 2014 Solid State Optronics • San José, CA

SMQ4101 Package Dimensions

16 PIN SOIC Package

Note: *All dimensions in inches ["] with millimeters in parenthesis (mm)*




© 2014 Solid State Optronics • San José, CA

SMQ4101 Package Dimensions

16 PIN SOIC Footprint


Note: *All dimensions in inches ["] with millimeters in parenthesis (mm)*




SMQ4101 Package Dimensions

TAPING SPECIFICATIONS (in millimeters)


Outline and Dimension (Tape)



Parts Orientation and Tape Direction




Outline and Dimensions (Reel)



Packaging: 1,000 pcs / reel

SMQ4101 Package Marking



DISCLAIMER

Solid State Optronics (SSO) makes no warranties or representations with regards to the completeness and accuracy of this document. SSO reserves the right to make changes to product description, specifications at any time without further notices.
SSO shall not assume any liability arising out of the application or use of any product or circuit described herein. Neither circuit patent licenses nor indemnity are expressed or implied.
Except as specified in SSO's Standard Terms & Conditions, SSO disclaims liability for consequential or other damage, and we make no other warranty, expressed or implied, including merchantability and fitness for particular use.

LIFE SUPPORT POLICY

SSO does not authorize use of its devices in life support applications wherein failure or malfunction of a device may lead to personal injury or death. Users of SSO devices in life support applications assume all risks of such use and agree to indemnify SSO against any and all damages resulting from such use. Life support devices are defined as devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when used properly in accordance with instructions for use can be reasonably expected to result in significant injury to the user, or (d) a critical component of a life support device or system whose failure can be reasonably expected to cause failure of the life support device or system, or to affect its safety or effectiveness.

© 2014 Solid State Optronics • San José, CA