SOLID STATE OPTRONICS



SYZ6040

DC Input
400V
Photo SCR / Thyristor

Description


The SYZ6040 consists of a single input AlGaAs LED optically coupled to a photo-sensitive SCR. Optical coupling provides high isolation levels (up to $5kV_{RMS}$) while maintaining low-level DC signal control capability. With high load voltage and low input current, the SYZ6040 is an ideal solution for driving SCRs, Triacs and Solid State Relays.

The SYZ6040 comes standard in a compact 6 pin DIP package making it ideal for high-density board applications.

Applications

- Home Appliances
- Motor / Drive Controls
- Solid State Relays
- Solenoid / Valve Controls
- Temperature Controls
- Dimmer Controls

Schematic Diagram



SYZ6040

Features

- Low Input Control Current (5mA MAX)
- High Blocking Voltage (400V)
- 400mA Maximum Continuous Current
- High Isolation Voltage (up to $5kV_{RMS}$)
- High Transient Immunity (dV/dt = 400V/μS MIN)
- Long Life / High Reliability
- RoHS / Pb-Free / REACH Compliant

Agency Approvals

UL/C-UL:	File # E201932
VDE:	File # 40035191 (EN 60747-5-2)

Absolute Maximum Ratings

The values indicated are absolute stress ratings. Functional operation of the device is not implied at these or any conditions in excess of those defined in electrical characteristics section of this document. Exposure to absolute Maximum Ratings may cause permanent damage to the device and may adversely affect reliability.

Storage Temperature	-55 to +125°C
Operating Temperature	-40 to +85°C
Continuous Input Current	50mA
Transient Input Current	400mA
Transient Output Current	10A
Reverse Input Control Voltage	5V
Input Power Dissipation	40mW
Output Power Dissipation	500mW
Solder Temperature – Wave (10sec)	260°C
Solder Temperature – IR Reflow (10sec)	260°C

Ordering Information

Part Number	Description
SYZ6040	6 pin DIP, (60/Tube)
SYZ6040-H	$5kV_{RMS}$ V_{ISO}, 6 pin DIP, (60/Tube)
SYZ6040-S	6 pin SMD, (60/Tube)
SYZ6040-HS	$5kV_{RMS}$, 6 pin SMD, (60/Tube)
SYZ6040-STR	6 pin SMD, Tape and Reel (1000/Reel)
SYZ6040-HSTR	$5kV_{RMS}$, 6 pin SMD, Tape and Reel (1000/Reel)

NOTE: Suffixes listed above are not included in marking on device for part number identification

© 2013 Solid State Optronics • San José, CA
www.ssousa.com • +1.408.293.4600

SYZ6040 /H/S/TR
Rev 2.00 (11/25/2013)
001761

Electrical Characteristics, T_A = 25°C (unless otherwise specified)

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions
Input Specifications						
LED Forward Voltage	V_F	-	1.2	1.5	V	I_F = 10mA
LED Reverse Voltage	BV_R	5	-	-	V	I_R = 10µA
Reverse Leakage Current	$I_{InRleak}$	-	-	10	µA	V_R = 5µA
Trigger (Must Operate) Current[1]	I_{InOn}	-	2.5	5	mA	I_O = 400mA
Output Specifications						
Forward Blocking Voltage	V_{DM}	400	-	-	V	R_{GK}=10kΩ, T_A=100°C, I_D=150µA
Reverse Blocking Voltage	V_{RM}	400	-	-	V	R_{GK}=10kΩ, T_A=100°C, I_R=150µA
Continuous Load Current	I_{DM}	-	-	400	mA	I_F = 5mA
Transient Surge Current	$I_{DM\ (PEAK)}$	-	-	10	A	T = 16µS
On-State Voltage	V_{TM}	-	1.1	1.4	V	I_F = 5mA, I_{DM} = 400mA
Forward Leakage Current	I_{DM}	-	1	10	µA	R_{GK}=10kΩ, T_A=100°C, V_{DM}=400V, I_F=0
Reverse Leakage Current	I_{RM}	-	1	10	µA	R_{GK}=10kΩ, T_A=100°C, V_{RM}=400V, I_F=0
Gate Trigger Voltage	V_{GT}	-	0.6	1	V	V_{FX}=100V, R_{GK}=27kΩ, R_L=10kΩ
Gate Trigger Current	I_{GT}	-	20	50	µA	V_{FX}=100V, R_{GK}=27kΩ, R_L=10kΩ
Critical Rate of Rise[2]	dV/dt	400	-	-	V/µS	-
Isolation Specifications						
Isolation Voltage	V_{ISO}	3750			V_{RMS}	RH ≤ 50%, t=1min
(-H Option)		5000	-	-		
Input-Output Resistance	R_{I-O}	-	10^{12}	-	Ω	V_{I-O} = 500V_{DC}

Note 1: Resistive load. For inductive loads, higher drive current is recommended

Note 2: This is for static dV/dt.

© 2013 Solid State Optronics • San José, CA

SYZ6040 Performance & Characteristics Plots, T_A = 25°C (unless otherwise specified)

Figure 1: *Maximum Load Current vs. Temperature*





Figure 2: *Typical Blocking Voltage Distribution* (N = 100, Ta = 25°C)



SYZ6040 Solder Temperature Profile Recommendations

(1) *Infrared Reflow:*

Refer to the following figure as an example of an optimal temperature profile for single occurrence infrared reflow. Soldering process should not exceed temperature or time limits expressed herein. Surface temperature of device package should not exceed 250ºC:




Figure 1

Process Step	Description	Parameter
A	Preheat Start Temperature (ºC)	150ºC
B	Preheat Finish Temperature (ºC)	180ºC
C	Preheat Time (s)	90 - 120s
D	Melting Temperature (ºC)	230ºC
E	Time above Melting Temperature (s)	30s
F	Peak Temperature, at Terminal (ºC)	260ºC
G	Dwell Time at Peak Temperature (s)	10s
H	Cool-down (ºC/s)	<6ºC/s

(2) *Wave Solder:*

Maximum Temperature:	260ºC (at terminal)
Maximum Time:	10s
Pre-heating:	100 - 150ºC (30 - 90s)
Single Occurrence	

(3) *Hand Solder:*


Maximum Temperature:	350ºC (at tip of soldering iron)
Maximum Time:	3s
Single Occurrence	

© 2013 Solid State Optronics • San José, CA

SYZ6040 Package Dimensions

6 PIN DIP Package


Note: *All dimensions in millimeters with inches [“] in parenthesis ()*





SYZ6040 Package Dimensions


6 PIN SMD Surface Mount Package (-S)

Note: *All dimensions in millimeters with inches [“] in parenthesis ()*










© 2013 Solid State Optronics • San José, CA


SYZ6040 Package Dimensions

6 PIN SMD Tape & Reel (-STR)

Note: *All dimensions in millimeters*




W	B	B1	P	P1	K	E	T	D	D1
16.00 ±0.1	10.50 ±0.1	10.30 ±0.1	12.00 ±0.1	4.00 ±0.1	5.00 ±0.1	1.75 ±0.1	0.40 ±0.1	1.50 ±0.1	1.50 ±0.1



L	M	N	O	Q	R	S
330.00	100.00	16.40 +0.2	2.00 ±0.1	13.00 ±0.2	2.00	10.00

SYZ6040 Package Marking



SYZ6040 Package Weights

Device	Single Unit	Full Tube (60pcs)	Full Pouch (10 tubes)	Full Reel (1000pcs)
SYZ6040-(H)	0.41	43	450	-
SYZ6040-(H)S	0.40	42	440	-
SYZ6040-(H)STR	0.40	-	-	880

Note: *All weights above are in GRAMS, and include packaging materials where applicable*

DISCLAIMER

Solid State Optronics (SSO) makes no warranties or representations with regards to the completeness and accuracy of this document. SSO reserves the right to make changes to product description, specifications at any time without further notices.
SSO shall not assume any liability arising out of the application or use of any product or circuit described herein. Neither circuit patent licenses nor indemnity are expressed or implied.
Except as specified in SSO's Standard Terms & Conditions, SSO disclaims liability for consequential or other damage, and we make no other warranty, expressed or implied, including merchantability and fitness for particular use.

LIFE SUPPORT POLICY

SSO does not authorize use of its devices in life support applications wherein failure or malfunction of a device may lead to personal injury or death. Users of SSO devices in life support applications assume all risks of such use and agree to indemnify SSO against any and all damages resulting from such use. Life support devices are defined as devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and (c) whose failure to perform when used properly in accordance with instructions for use can be reasonably expected to result in significant injury to the user, or (d) a critical component of a life support device or system whose failure can be reasonably expected to cause failure of the life support device or system, or to affect its safety or effectiveness.